

## FINISH DESCRIPTION

### **Durable Eggshell Finish**

A premium eggshell finish that attracts attention but repels scuffs and stains. ScrubTough's durable polyurethane formula withstands regular cleaning and keeps walls looking their best.

## FEATURES

## BENEFITS

### **Finish Effect**

Rich, durable eggshell

### **Polyurethane Formulation**

Exceptional durability and cleanability

### **Unlimited Colors**

Choose any color from any fandeck

### **Easy Application**

Any quality painting contractor can apply - Brush, roll or spray

### **Quick Order Shipment**

Most orders (even customs) ship within 3 days

### **Waterbased / Low VOC**

Low odor spray application meets all environmental requirements

### **Warranty**

5 – Year manufacturer's warranty against adhesion failure if product is correctly applied

### **Class A fire rated**

Like all Scuffmaster paints, ScrubTough is Class A fire rated.

## WHERE TO SPECIFY SCRUBTOUGH

Remember that Scuffmaster Paints are designed for wall surfaces yet can be applied to display fixtures, elevator doors, stairway frames, columns and other architectural elements besides conventional walls.

**Corporate Spaces**

Corridors  
Offices  
Lobby areas  
Conference rooms  
Cafeterias  
Lunch rooms  
Bathrooms  
Stairwells

**Educational Facilities**

Corridors  
Offices  
Lecture halls  
Auditoriums  
Gymnasiums  
Locker rooms  
Bathrooms  
Dormitories

**Healthcare Facilities**

Corridors  
Offices  
Waiting areas  
Examination rooms  
Meeting rooms  
Cafeterias  
Bathrooms  
Stairwells

**Other Applications**

Theaters  
Exercise rooms  
Pool areas  
Escalator areas  
Elevator areas  
Passenger terminals  
Baggage claim areas

**Suitable Substrates:**

Primed sheetrock, previously painted surfaces, concrete block, metal, ceramic tile, glazed block and others.

**Application:**

Finish can be brushed, rolled or sprayed. Call your Scuffmaster distributor or ICP for details and applicators in your area (800) 898-0219.

**Custom Colors:**

Yes. No up-charge. Contact your Scuffmaster distributor.

**TECHNICAL INFORMATION****System Components**

Finish Coat

**Finish Appearance**

Rich eggshell

**Colors Available**

Can match any color from any fandeck

**Application**

Finish can be brushed, rolled or sprayed. Call your Scuffmaster distributor or ICP for details and applicators in your area (800) 898-0219.

**Coverage Rates**

Approximately 350 ft/gal. (deep/bright colors require additional coats)

**Maximum VOC**

50 g/L

**Fire Rating**

Class A or I

ASTM E-84-91a

**Scrub Resistance:**

8,000 Scrub Cycles

ASTM D 2486

**Stain Removal:**

Excellent Rating for most stains

4-Hour Open Spot Test

**FIVE YEAR LIMITED WARRANTY**

ICP Building Solutions Group warrants the Scuffmaster components of this finish system against manufacturing defect for a period of five years from the date of application when applied to a wall surface according to manufacturer's printed instructions. Manufacturing defect is defined to be a failure of the coating system to adhere to a wall surface when applied according to manufacturer's printed instructions, and does not include subsequent failure or damage caused by exogenous factors such as substrate failure or defect, sharp objects, persons, or acts of God. In the event of a failure resulting from manufacturing defect, the product will be replaced. ICP Building Solutions Group shall have no obligation to or otherwise participate in labor or other costs associated with replacing the product. This warranty supersedes all previous warranties.

## SAFETY INFORMATION

Some persons may experience an allergic reaction to paint products if exposed to spray mist. Because spray application of this Scuffmaster finish may create a fine mist of product and product catalyst in the immediate application area, a high-efficiency particulate respirator and protective glasses or goggles should be worn by the applicator. The immediate application area should be "cautioned-off" to prevent persons without safety equipment from coming into contact with mist. Ensure good ventilation. Product MSDS sheets are available from ICP by calling (800) 898-0219.

First Aid: Ingestion – induce vomiting, consult a physician. Skin contact – wash with soap and water. Eye contact – immediately flush with clean water for 15 minutes occasionally lifting eyelids. If contact lenses are worn, remove lenses and continue rinsing. Clean lenses before reusing - may not be possible to reuse. Obtain medical attention. Refer to product MSDS and crosslinker MSDS. In case of emergency, call 800-535-5053.

## HOW TO SPECIFY SCRUBTOUGH

Specifying a Scuffmaster ScrubTough finish is easy.

1. Call out the Scuffmaster finish color number in your finish schedule or on drawings. Scuffmaster color numbers are printed below each color chip in standard sample cards and on the reverse of every custom sample.
2. Call out the Scuffmaster system components required for the substrate being painted in the "products" section of your specification. The Scuffmaster ScrubTough finish system for common substrates are listed below.

**IMPORTANT:** ICP strongly recommends including proper applicator qualification submittal procedures, finish submittal procedures and surface preparation steps in your specification. Please refer to the guide specifications for this language.

## SCRUBTOUGH FINISHES FOR PROPERLY PREPARED SURFACES

For more detailed information refer to the Guide Spec.

### **1. New Sheetrock:**

Primer - 1 coat Scuffmaster Primemaster Primer/Sealer

1-2 coats of Scuffmaster ScrubTough Performance Paint (at least 2 coats if bright, deep or dark color)

### **2. Cured Concrete/Masonry:**

Primer - 1 coat of 100% acrylic block filler (if required to seal surface for better coverage)

1-2 coats of ScrubTough Performance Paint with (at least 2 coats if bright, deep or dark color)

### **3. Wood**

Primer – Spot-prime knots and prime with 1 coat of a suitable stain-blocking primer

1-2 coats of ScrubTough Performance Paint with (at least 2 coats if bright, deep or dark color)

### **4. Hard Shiny Surfaces:**

Primer - 1 coat of Scuffmaster Primemaster Bonding Primer

1-2 coats of ScrubTough Performance Paint (at least 2 coats if bright, deep or dark color)

### **5. Previously Painted Surfaces:**

Primer - Apply suitable primer. Call ICP.

1-2 coats coat of ScrubTough Performance Paint (at least 2 coats if bright, deep or dark color)

## CLEANING INSTRUCTIONS

Allow product to cure for at least seven days following application (allow 28 days on hard, non-absorbent substrates) before applying cleaning chemicals. Most common stains can be removed using warm water and detergent. More difficult stains may require stronger cleaners and a light abrasive pad. Before using a new cleaner for the first time, test its effect on the finish by applying in an inconspicuous area as a small amount of paint may also be removed during the cleaning process.

